MGT 23

Color enhancer for rough surfaces

Wet effect color enhancer suitable for all natural stone, limestone, sandstone, marble, granite with rough, bushhammered, sandblasted, flamed finish. Protects from dirt and offers a good water-repellence. The product does not turn yellow and is resistant to wear.



Coverage: 1 litre for approx. 17 - 20 m2 depending on the finish of the surface and on its absorption.



Strong Points

- Revives the natural colour of the surface
- Not film forming
- Does not turn yellow
- Protects from dirt
- Water repellent

- Anti stain
- Anti oil
- Makes the cleaning easier
- Strengthening effect
- Antidirt effect
- Antisalt effect

Application

SHAKE BEFORE USING

READY TO USE PRODUCT, DO NOT DILUTE.

On clean and dry surfaces apply MGT 23 directly onto the surface and spread it out evenly with a microfiber cloth or a mop with circular motions. Allow to dry.

We recommend to apply small quantities of product in more coats instead of one copious coat.

The obtained result is not reversible.

Depending on the absorption and on the desired effect apply 2 or 3 coats at a distance of 5-6 hours one from another. If the surface is very rough apply with a low pressure gun.

Wait at least 48/72 hours before carrying out staining tests, so to allow the product to dry in the porosity of the surface.

For the ordinary maintenance of the treated surface we recommend the regular use of MGP 24 detergent.

Warnings

Before using the product, read the toxicological data sheet (MSDS) and the label detailing all risks and the personal protective equipment to be used for a correct use. The data of this technical data sheet is based on reliable information. Despite of this, the manufacturer can't know in advance the condition of the materials to be processed and the way of use of the product. Therefore, he disclaims any and all responsibility for damage arising from inadequacy of the product for special applications.

Before treating or cleaning surfaces, carry out a test on an invisible point to prevent possible damages, since our responsibility is limited to the warranty of the purchased product and therefore we disclaim any responsibility for damages resulting from negligence or wrong use.

Packaging and Storage

Keep the original, sealed container in covered, ventilated, dry environment and keep away from heat or low temperatures. After the use keep the package well closed, so the product has a shelf life of approx. 36 months. Box of 15 x 1 litre bottle – Box of 4 x 5 liter cans

