

TEC 40

Protector for hard and absorbing surfaces.
Specific for quartzites.

Water-and-oil repellent protector for hard and absorbing surfaces like quartzites, with polished or honed finish. Protects the surfaces from staining substances like oil, coffee, grease. It protects from dirt in general and makes cleaning easier. Specific for kitchen countertops, tables, floors and coatings.



Coverage: 1 litre for approx. 20-30 m2 depending on the finish of the surface and on its absorption.

Strong points

- Anti stain
- Anti oil
- Water repellent
- Anti garffiti
- Anti marker
- Does not turn yellow
- Makes the cleaning easier
- Very good protection on quartzites
- High concentration
- Suitable for honed and polished surfaces

Application



SHAKE BEFORE USING READY TO USE PRODUCT, DO NOT DILUTE.

Polished surfaces: evenly apply with a microfiber cloth with circular movements. After being applied, the product leaves a slightly greasy residue; allow to dry for about 24 hours before removing the surplus with paper or a dry cloth. **Honed surfaces:** evenly apply with a microfiber cloth with circular movements. Allow to dry for about 1 hour. The product will be absorbed but not evenly, so within 1 hour wipe the surface with a microfiber cloth in order to uniform the application and eliminate the surplus. Allow to dry.

Automatic production lines:

Pour a few drops of product vertically on the surface and even with a first soft nylon brush. Then even with two nylon brushes so to allow the product to penetrate into the porosity and finally use two brushes with fabric felt to eliminate the residue.

TEC 40 is a concentrated product, after the brush cycle a very light residue may remain on the surface, which will dry within a few days without creating problems on the surface. We suggest a max line speed. 1 meter per minute to allow the product to act on the surface. This is only a rough indication, we suggest carrying out specific tests according to production needs.

Wait at least 48/72 hours before carrying out staining tests, so to allow the product to dry in the porosity of the surface.

For the ordinary maintenance of the treated surface we recommend the regular use of MGP 24 detergent.

Tests and results

To watch the video click on the image or use this link: <https://youtu.be/hUT0E12V7nw>



Useful information

Since our goal is maximum customer satisfaction, we specify the following. The lasting of a protector on interior surfaces is longer than on exterior surfaces which are more subject to UV rays, temperature excursions and records. We also specify that the fact that a protective is defined as stain resistant does not mean that the surface will never get stained, but that it is possible to obtain the best in terms of results and protection when the substance that has accidentally fallen on the surface is removed as soon as possible. Furthermore, to get the best from surfaces of any kind and material, our suggestion is to choose cleaning products that respect both the surfaces and the treatments and carry out correct maintenance cycles. In this regard, we suggest you download the various guides on the use and maintenance of surfaces to extend the life and maintain the beauty of your surfaces over time from the download area of our site.

Warnings

Before using the product, read the toxicological data sheet (MSDS) and the label detailing all risks and the personal protective equipment to be used for a correct use. The data of this technical data sheet is based on reliable information. Despite of this, not knowing either the materials to be treated nor their conditions, the specific characteristics, the processes and finishes they have undergone, the conditions of the treated materials and the way in which the product will be used, we decline any and all responsibility for damage arising from inadequacy of the product for specific and particular applications.

Therefore, before using the product, carry out a test on an invisible area of the surface and only when sure about the success, proceed on a larger area.

Our responsibility is limited to the cost of the purchased product and therefore we are not liable for damages resulting from negligence or incorrect or different use of the product, from not following these warnings or by other factors that do not depend on the product itself.

Packaging and storage

Keep the original, sealed container in covered, ventilated, dry environment and keep away from heat or low temperatures. After the use keep the package well closed, so the product has a shelf life of approx. 36 months.

Box of 15 x 1 L bottle. Box of 4 x 5 L cans.

Guarantee

If the customer's request is to have a guarantee on a specific material or project, just send us the request and we will evaluate and, if necessary, adapt the best guarantee to a specific material or specific project, thus also indicating the various conditions that change from situation to situation. We would like to point out that although several products offer generalized guarantees that boast long duration, it is advisable to be wary of generic guarantees that do not consider specific aspects such as: specific materials, conditions and environment where these will be placed and the final use of the environments. For more information read chapter 5 of our EBOOK at the link: <https://www.mptreatment.com/it/brochure/ebook.html>

Application accessories



Click on the image or go to the below link to watch the application video: <https://youtu.be/3S1HEcRs2>

Application accessories for honed or polished surfaces



www.mptreatment.com

Made in Italy Products



MASSIMO PIRACCINI srl

Sede Legale: Via Santa Croce 477 – 47032 Bertinoro (FC) Italy
Unità Amministrativa: Via Marco Uccellini 22 – 47034 Forlimpopoli (FC) Italy
Tel. +39 0543 745268 Fax +39 0543 745644
www.mptreatment.com info@mptreatment.com export@mptreatment.com

